

DECONTAMINATION & SHELTERS

PERSONAL PROTECTIVE EQUIPMENT



RAPID PRO SHELTER 50-7 & 50-9

The RP 50 shelter ranges are large sized rapid deployment shelters in a highly portable and light-weight package. The standard models have multiple entry/exit points with side mesh windows and cover flaps. The shelters can be used for casualty management, surge capacity, temporary accommodation, situation management, or other mobile shelter needs. The shelter is available in two standard lengths RP50-7 & RP50-9. The shelters require four persons for deployment.







SPECIFICATION

Repair kit & anchor kit x 1 of each
Transport bag x 1
Shelter Raising poles x 3
Flat ground sheet x 1

Flat ground sheet x 1
Standard Features 4 x Heater Ports

2 x Single zip end doors

2 x Windows

1 x Side door (50-9 only)

External Dimensions (Approx)

RP 50-7 : L 524 x W539 x H 311 cm RP 50-9 : L 673 x W539 x H 311 cm

Internal Dimensions (Approx)

RP 50-7 : L 524 x 485 x H 284 cm RP 50-9 : L 673 x 485 x H 284 cm

Storage Size (Approx)

RP 50-7 & RP50-9: 100 x 100 x 100 cm

Weight Packed (Approx)

RP 50-7: 103.5kg RP 50-9: 130.5kg

*Additional Accessories Options Available

- Articulating internal frame with locking straps allows high speed deployment with high system integrity.
- Highly corrosion resistant construction grade aluminium frame with alochrome treatment and polyester powder coated tubes.
- Highly flexible, tear resistant, UV stabilized and fire retardant fabric available in a choice of colours.
- Windows provide warm-weather, ventilation and ambient lighting.
- 2 Panelled zipped end doors.
- Colour options: Red, Blue, Yellow, White & Blue
- Standard extra features available; Turn up ground sheet, Side Banners, Clear window covers POA.

| Doc. Control: | Rev.: | Date: |
|---------------|-------|----------------|
| | 3.2 | April 12, 2016 |

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT DS 1709-3.2



FEATURES