

AV-FS12L CLEAR FACE SHIELD

Article No.: 3417AV380

The AV-FS12L Clear Molded Lexan Face Shield with Universal hole pattern. AV-FS12L fits AV-VB10/20/30. Plus wraparound, splash and impact protection!



TECHNICAL SPECIFICATIONS

Heat Resistance : 265°C
Material : Molded Aspherical Lexan
Color : Clear
Thickness : 0.07 inches
Dimensions : 8" x 12" x 0.07"
Light Transmission : VLT = 91%
 UV protection = 100.0% / 180-380 nm
 IR protection = 8%

Standard: ANSI Z87.1-2010

Note: ANSI standard requires users to wear safety glasses under face shields.

Features: Faceshield has Universal Hole Pattern for: Headgear - fits AV-HG25 / AV-HG35 headgear Safety helmet – faceshield fits "AV-VB" visor brackets with "AV-SA" slot adaptor for mounting on most slotted safety helmets.

Application:

For industrial use to provide impact, splash, and 99.9% UV protection. Polycarbonate (PC) and Lexan (L & LG) materials are heat tolerant material.



AV-VB10 Visor Bracket
Article No.: 3481AV392



AV-SA29 Slot Adapters
Article No.: 34182AV394

Doc. Control:	Rev.: 3.2	Date: April 5, 2016
----------------------	-----------	---------------------

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT EF 2015-3.2