

# 🛞 INHERENTLY HEAT & FLAME RETARDANT

PERSONAL PROTECTIVE EQUIPMENT



## **BOMBER WINTER JACKET** Article No.: 0307FT50-BWJ

**Flash Armor**<sup>®</sup> inherently flame-retardant and high temperature resistant garments do not support cumbustion in the air, melt or drip due to their molecular structure and its flame retardant characteristics cannot be washed away. Our range is designed to cater for working conditions around the world as garments are offered in various designs and options.

Flame resistant clothing made with **Flash Armor**<sup>®</sup> provides valuable peace-of-mind, which enables those who wear it to focus on the job at-hand & perform to their fullest potential.



A breathable workwear with properties of inherent heat & flame retardant. This garment is a preferred choice of people working from the oil & gas, petrochemical, refinery industries, as well as an excellent choice for electric and power generation industries.

Inherently flame resistant – FR properties are built in and won't wash or wear out. Comfortable to wear - Soft & breathable. Roomy sizing patterns allow for a great fit.

Exceptional durability – Outstanding laundered appearance - Fabric retains its like new look and maintains permanent pressed appearance. Excellent Value – Long life cycle & great durability.

### COMPOSITION

Outer & Inner Shell: Dupont<sup>™</sup> Nomex<sup>®</sup> Delta C.A. Fabric Weight: 4.5 oz or 150 gsm Middle Layer: Perforated FR membrane 1.5 oz or 50 gsm (Moisture Barrier & Wind Breaker) Lining: Inherently FR Fleece - 7.3 oz or 250 gsm

#### **STYLE & DESIGN**

- Heavy duty metallic zipper and full velcro flap closure
- Two front lower slant pockets with zipper
- Two chest pockets with flap button closures
- Two inside pockets
- Mic loop on the right chest
- Rolled collar
- Detachable hood
- Adjustable cuffs
- Elasticated side waist with drawstrings
- FR reflective tapes on front, back and arms
- Bar tacked stress points
- Double stitched with FR Thread
- Colour fastness 4-5 & Easy care



### **INTERNATIONAL STANDARDS**

• EN ISO 11612:2008 (A1 - Limited Flame Spread, B1 - Convective Heat, C1 - Radiant Heat)

EN ISO 11612 A1. B1. C1

- EN 1149-5:2008
- NFPA-2112
- ASTM D 6413-99
- ASTM D 737
- ATPV 4,1 cal/cm<sup>2</sup> HRC 1

 Rev.:
 Date:

 3.2
 March 30, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FR 6007-3.2

EN ISO 1149-5

overed strictly

Nomex.

PARTNER



FLOWTRONIX (FT)

WWW.FLOWTRONIX.COM

NFPA

2112

WE ARE TRUSTED TO DELIVER QUALITY

# 👋 INHERENTLY HEAT & FLAME RETARDANT

PERSONAL PROTECTIVE EQUIPMENT



FLOWTRONIX (FT)

WWW.FLOWTRONIX.COM

WE ARE TRUSTED TO DELIVER QUALITY