

PERSONAL PROTECTIVE EQUIPMENT



FIELD WINTER JACKET Article No.: 0341FT01-FWJ

Flash Armor[®] inherently flame-retardant and high temperature resistant garments do not support cumbustion in the air, melt or drip due to their molecular structure and its flame retardant characteristics cannot be washed away. Our range is designed to cater for working conditions around the world as garments are offered in various designs and options.

Flame resistant clothing made with **Flash Armor**[®] provides valuable peace-of-mind, which enables those who wear it to focus on the job at-hand & perform to their fullest potential.





INTERNATIONAL STANDARDS

- Garment is certified to **EN ISO 11612:2008 A1 A2 B1 C1 F1** Protective clothing - to protect against heat and flame.
- ARC thermal protection (ATPV): HRC 1
- EN 1149-5:2008
- EN 61482-1-2
- EN 340:2003

 Rev.:
 Date:

 3.2
 March 30, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FR 6280-3.2

EN ISO 11612 A1, A2, B1, C1, F



PYXIS® is an inherent heat and flame resistant fabric that provides optimum

protection against flash fire and electric arc flash. Engineered to the highest level of strength, durability and comfort, **PYXIS®** is suitable for oil and gas, petrochemical, fire service, electrical maintenance, steel and welding.

COMPOSITION

Fabric Grade: PYXIS MDC 200 Composition: 49% Modacrylic / 42% Cotton/ 5% Para-aramid / 3% Nylon / 1% Antistatic Fabric Weight: 200 gsm / 6.0 oz Middle Layer: Perforated FR membrane 1.5 oz or 50 gsm (Moisture Barrier & Wind Breaker) Inner Lining: Inherently FR Fleece - 7.3 oz or 250 gsm

STYLE & DESIGN

- Heavy duty metallic zipper, snap button and storm flap closure fully concealed
- Two front lower side slant pockets
- · Pencil slot on left sleeve
- Mic loop on the right chest
- Rolled collar
- Detachable hood
- One inside pocket with closure
- Adjustable cuffs
- Elasticated side waist
 All stress points are bar tack

EN ISO 1149-5

- All stress points are bar tacked
 Double stitched with Nomex[®] Thread
- Colour fastness 4-5 & Easy care



. OUTER LAYER: Abrasion resistant FR face MIDDLE LAYER: FR membrane - Blocks v enhances breathability

ly FR Comfor

NFRIIN

A PRODUCT OF A PRODUCT OF PROTECTIVE LINE

FLOWTRONIX (FT)

WWW.FLOWTRONIX.COM

WE ARE TRUSTED TO DELIVER QUALITY



FLOWTRONIX (FT)

WWW.FLOWTRONIX.COM

WE ARE TRUSTED TO DELIVER QUALITY